



**MEDIDAS Y PESO POR METRO / CANTO VIVO Y CANTO REDONDO  
ASTM B187 - C11000**

Medidas				Peso por Metro	Peso total
Pulgadas		Milímetros			
Espesor	Ancho	Espesor	Ancho		
1/8	1/4	3.1750	6.350	0.18	0.659
1/8	3/8	3.1750	9.525	0.27	0.988
1/8	1/2	3.1750	12.700	0.359	1.314
1/8	5/8	3.1750	15.875	0.449	1.643
1/8	3/4	3.1750	19.050	0.539	1.973
1/8	1	3.1750	25.400	0.719	2.632
1/8	1 1/4	3.1750	31.750	0.898	3.287
1/8	1 1/2	3.1750	38.100	1.078	3.945
1/8	2	3.1750	50.800	1.437	5.259
1/8	3	3.1750	76.200	2.160	5.259
3/16	1/2	4.7625	12.700	0.539	1.973
3/16	3/4	4.7625	19.050	0.809	1.973
3/16	1	4.7625	25.400	1.078	2.467
3/16	1 1/4	4.7625	31.750	1.348	4.934
3/16	1 1/2	4.7625	38.100	1.617	4.934
3/16	2	4.7625	50.800	2.156	7.891
3/16	3	4.7625	76.200	3.234	11.836
3/16	4	4.7625	101.600	4.312	15.782
1/4	1/2	6.3500	12.700	0.719	2.632
1/4	5/8	6.3500	15.875	0.898	3.287
1/4	3/4	6.3500	19.050	1.078	3.945
1/4	1	6.3500	25.400	1.437	5.259
1/4	1 1/4	6.3500	31.750	1.798	6.581
1/4	1 1/2	6.3500	38.100	2.156	7.891
1/4	2	6.3500	50.800	2.875	10.523
1/4	2 1/2	6.3500	63.500	3.594	13.154
1/4	3	6.3500	76.200	4.312	15.782
1/4	4	6.3500	101.600	5.75	21.045
1/4	5	6.3500	127.000	7.188	26.308
1/4	6	6.3500	152.400	8.625	31.568



Z & E TECHNOLOGIES

# SOLERAS DE COBRE



**MEDIDAS Y PESO POR METRO / CANTO VIVO Y CANTO REDONDO  
ASTM B187 - C11000**

Medidas				kg/m	Peso total (kg)
Pulgadas		Milímetros			
Espesor	Ancho	Espesor	Ancho		
3/8	3/4	9.5250	19.050	1.618	5.922
3/8	1	9.5250	25.400	2.156	7.891
3/8	1 1/4	9.5250	31.750	2.695	9.864
3/8	1 1/2	9.5250	38.100	3.235	11.840
3/8	2	9.5250	50.800	4.313	15.786
3/8	2 1/2	9.5250	63.500	5.391	19.731
3/8	3	9.5250	76.200	6.469	23.677
3/8	3 1/2	9.5250	88.900	7.546	27.618
3/8	4	9.5250	101.600	8.625	31.568
3/8	5	9.5250	127.000	10.78	39.455
3/8	6	9.5250	152.400	12.936	47.346
1/2	1	12.7000	25.400	2.875	10.523
1/2	1 1/4	12.7000	31.750	3.594	13.154
1/2	1 1/2	12.7000	38.100	4.413	16.152
1/2	2	12.7000	50.800	5.750	21.045
1/2	2 1/2	12.7000	63.500	7.188	26.308
1/2	3	12.7000	76.200	8.625	31.568
1/2	3 1/2	12.7000	88.900	10.063	36.831
1/2	4	12.7000	101.600	11.501	42.094
1/2	5	12.7000	127.000	14.375	52.613
1/2	6	12.7000	152.400	17.250	63.135
3/4	2	19.0500	50.800	8.625	15.786
3/4	3	19.0500	76.200	12.938	31.568
3/4	4	19.0500	101.600	17.250	47.353
1	2	25.4000	50.800	11.480	42.017
1	3	25.4000	76.200	17.210	62.989

CARACTERÍSTICAS ESPECÍFICAS: SOPORTA DOBLECES MAYORES A 90° / CAMBER (STRAIGHTNESS) MENOR A 1/32" PULIDO Y LUBRICADO NO.4 (EXCELENTE APARIENCIA Y FUNCIONALIDAD) / CONDUCTIVIDAD MÍNIMO DE 101 IASC





**REFERENCIA EN MILÍMETROS / PESOS UNITARIOS KG/M CANTO VIVO  
ASTM B187 - C11000**

Espesor	Ancho	kg/m	Peso total	Espesor	Ancho	kg/m	Peso total (kg)
8	10	0.711	2.602	10	10	0.889	3.254
8	12	0.853	3.122	10	12	1.067	3.905
8	15	1.067	3.905	10	15	1.334	4.882
8	20	1.422	5.205	10	20	1.778	6.507
8	25	1.778	6.507	10	25	2.223	8.136
8	30	2.134	7.810	10	30	2.667	9.761
8	40	2.845	10.413	10	40	3.556	13.015
8	50	3.556	13.015	10	50	4.445	16.269
8	60	4.267	15.617	10	60	5.334	19.522
8	75	5.334	19.522	10	75	6.668	24.405
8	80	5.690	20.825	10	80	7.112	26.030
8	100	7.112	26.030	10	100	8.890	32.537
8	120	8.534	31.234	10	120	10.668	39.045
8	125	8.890	32.537	10	125	11.113	40.674
8	150	10.668	39.045	10	150	13.335	48.806
8	160	11.379	41.647	10	160	14.224	52.060
Espesor	Ancho	kg/m	Peso total	Espesor	Ancho	kg/m	Peso total (kg)
12	10	1.067	3.905	15	10	1.334	4.882
12	12	1.280	4.685	15	12	1.600	5.856
12	15	1.600	5.856	15	15	2.000	7.320
12	20	2.134	7.810	15	20	2.667	9.761
12	25	2.667	9.761	15	25	3.334	12.202
12	30	3.200	11.712	15	30	4.001	14.644
12	40	4.267	15.617	15	40	5.334	19.522
12	50	5.334	19.522	15	50	6.668	24.405
12	60	6.401	23.428	15	60	8.001	29.284
12	75	8.001	29.284	15	75	10.001	36.604
12	80	8.534	31.234	15	80	10.668	39.045
12	100	10.668	39.045	15	100	13.335	48.806
12	120	12.802	46.855	15	120	16.002	58.567
12	125	13.335	48.806	15	125	16.669	61.009
12	150	16.002	58.567	15	150	20.003	73.211
12	160	17.069	62.473	15	160	21.336	78.090

CARACTERÍSTICAS ESPECÍFICAS: SOPORTA DOBLECES MAYORES A 90° / CAMBER (STRAIGHTNESS) MENOR A 1/32" / PULIDO Y LUBRICADO NO.4 (EXCELENTE APARIENCIA Y FUNCIONALIDAD) / CONDUCTIVIDAD MÍNIMO DE 101 IASC

\* FABRICAMOS LARGOS Y TEMPLES ESPECIALES DE ACUERDO A VOLÚMEN.